

RECYCLING ROLL-OFF CONTAINER SPECIFICATIONS  
(1-Bin Containers w/Steel Loading Doors)

**General:**

1. Containers shall be enclosed.
2. Containers shall be compatible with the “hook” type (AMPLIROLL) system, in use at the Wayne County Recycling Center, as well as the conventional cable-type system.
3. Containers shall be constructed utilizing what’s known in the industry as “gabrel”, “hip” or “barn-style” roofs.
4. Containers shall allow for emptying of compartment, from the rear.
5. Containers shall be (20) feet in length and have (25) cubic yard capacity.
6. Front and rear wheels (rollers): 8”X10” long rear - 8”X6” long front, equipped with grease fittings.
7. 3/16” floor sheets (2- pieces).
8. Understructure: 3”X 4.1 lbs./ft. channel. 16” centered cross members.
9. Sides and roofs of containers shall be constructed of (10) gauge steel (minimum).
10. Tailgate latch with vertical lift handle.
11. (2) Heavy-Duty machine type tailgate hinges (on passenger side of container).
12. Containers shall be designed so that precipitation cannot enter the material loading doors when they are closed.
13. A one-half inch metal drip edge shall be installed above material loading doors (full length of container) to prevent precipitation from entering compartments.
14. Exterior of containers (including floor) shall be coated with a rust inhibitive primer and (2) coats of heavy-duty enamel (Forest Green). Interior surfaces shall be coated with a rust inhibitive primer.
15. Each bidder shall provide a drawing or photograph of the container as proposed, showing the location of the material loading doors and shape of the container.

**Compartments:**

16. Containers shall be open (one compartment), with no compartment doors (dividers).
17. The compartment shall have drainage to prevent the puddling of liquid on the compartment floors.

**Material Loading Doors:**

18. There shall be three (3) material loading doors spaced evenly on the top-side of the container. The doors shall be heavy duty and made of steel. They shall be adequately-sized to allow for the loading of cardboard.
19. All doors shall be on the same side (passenger side) of the container.
20. All doors shall be placed on the top-side of the container, to allow the compartment to be filled completely.
21. All doors shall be equipped with a locking system that utilizes two (2) horizontal metal bars that cover the doors and prevent them from being opened. One metal bar will be long enough to cover (2) of the loading doors, while the other metal bar will be sized to cover the remaining door. Padlocks will be used, but are not to be included in the bid.

RECYCLING ROLL-OFF CONTAINER SPECIFICATIONS  
(1-Bin Containers w/Steel Loading Doors)

**Delivery:**

22. Guaranteed delivery shall be (8) weeks or sooner from the date of award.
23. At least (48) hours advanced notice of delivery shall be provided during the normal work week by telephoning the Wayne County Recycling Center at (570)-253-9727. Contact person is Randy S. Heller.

*\*NOTE: Please include a copy of any company literature you may have on containers, listing general specifications and materials used in their construction.*